



PROFESSIONAL TESTING LABORATORY, INC.

TEST REQUEST FORM

COMPANY NAME		DATE	/ /
ADDRESS		PO#	
CITY/STATE/ZIP		RETAIN TEST SAMPLES *	Y/N
PHONE		RETAIN LEFTOVERS*	Y/N Bin#
EMAIL/FAX		PRIORITY/RUSH	Y/N
AUTHORIZED BY		NEED RESULTS BY	/ /

***TEST RETAINS ARE KEPT FOR A MAXIMUM OF 1 WEEK.**

IF YOU NEED SAMPLES RETURNED THERE WILL BE AN ADDITIONAL CHARGE FOR SHIPPING.

DESCRIPTION OF TEST SAMPLE

Identification		Construction	
Color		Fiber	
Roll		Backing	
REFERENCE:		SPECIAL INSTRUCTIONS:	

Physical	Flammability	Colorfastness	Wear/Perf	Vinyl
Delamination	Pill	Light ()	Roll Chair	ASTM F2055/F2421
Tuft Bind	Panel	Ozone ()	Taber	ASTM F970
Dim. Stability	NY Panel	NO2 ()	Vetterman	James Machine
Edge Ravel	Smoke – flaming	Burnt Gas ()	Hexapod	ASTM F925
Break Load/Elong	Smoke – non flaming	Crocking	Wheel Chair	ASTM F137
Comp. Rec.	FMVSS 302	AATCC 107	Contract Walker	ASTM F1914
Tear Strength	FAA Horizontal	AATCC 175 (reg/GSA)	Stat. Coeff	ASTM F2199
CONSTRUCTION	Tunnel Test	Bleach	Odor	ASTM F386
Pile Wt.	YARN	Stain (Comm/Res)	Aachen (edge curl)	ASTM F410
Density	Ext. Matter	AATCC 171	Pilling/Fuzzing	ASTM F1514/F1515
Latex Wt.	Fiber ID	WOOD	Bundle Wrap	ASTM F2753
Total Wt.	Fiber ID w/photo	Falling Ball	Velcro	ASTM D4060
Backing Wt.	Melt Point	D3459 Humid Dry Cyc	Acc. Soiling	ASTM F1066 VCT
Total Thickness	Yarn Size/Ply/Twist	HPVA Bond Line	Water Penetration	ASTM F1303VinSheet
Pile Thickness	Tensile/Elong	D1037 Water Abs.	British Spill	ASTM F1303 VinSq
Pile Ht/ Tuft Length	Moisture Content	D3359 Finish Adhes.	Heel Rub	NALFA
Stitch/Gauge	CHEMICAL	STATIC		
Tufts/sq inch	Specific Gravity	Static (w/wash)	AUTOMOTIVE	MISC
	Ash Content	Static (step)	Nissan	Anti Microbial
WOOD/VINYL	Chlorides	IBM/Burroughs	GM	ASTM C518
Formaldehyde	Urine/Creatinine	ESD S7.1	Chrysler	CAL 1350
	pH	Static Decay	Subaru	
	Fluorine			
	Plasticizer			BATTERIES
				GSA
				FHA

714 Glenwood Place

Dalton, GA 30721

Phone 706-226-3283 Fax 706-226-6787

email: protest@optilink.us